Mud Sucker® **Diaphragm Pumps**

B Series

Solids Crushing Diaphragm Pumps

E 4B-EC™ Standard Piping

3B-EC™ **In-line** Piping





Performance Range

Max. capacity	110 GPM	
Max. suction lift	25'vertical or 75' horizontal	
Max. discharge head	50' vertical or 300' horizontal	
Solids handling	2¼" dia or 50% by volume	

Pump and Motor Specifications

Suction inlet/outlet size	4"x4"			
Max. liquid temperature	104°F (40°C) continuous Cast iron (ASTM A356, Class 30)			
Pump body casing				
Diaphragm	14¾" dia thermoplastic elastomer (red) Severe duty -25°F to 212°F Optional: Neoprene			
Ball valves	5-1/8" diameter polyurethane with steel core			
Gearbox	Helical bevel cast iron housing with heat treated gears			
Hardware	Zinc plated			
Rod end bearing body	Cast iron, protective coated for corrosion resistance			
Ball bearing	Cast iron , protective coating for corrosio resistance			
Ultimate radial static load capacity	9,000 Lbs			


Motor Options

Part No.	Motor Option
61737-00	5 hp, 1800RPM/3/60/230-460V
61737-10	5 hp, 1800RPM/1/60/230V
61737-20	5 hp, 1800RPM/3/60/230-460V
61737-30	3 hp, 1800RPM/1/60/115-230V
	61737-00 61737-10 61737-20

FEATURES 4" Connection size Pump up to 110 GPM Transfer spherical solids up to 2 1/4" or 50% by volume Pump up to 50° vertical or 300' horizontal 143/4" heavy duty diaphragm Multiple drive options and industry specific components.

.....

PROFESSIONA



Professional Options for Professional Applications





.....

Wastewater Containment System

4B Series - Trolley Mounted

4B Series - Trailer Mounted

Mud Sucker[®] Diaphragm Pumps

Toll-Free North America 1.888.829.2783

Worldwide 201.445.2882

Website http://www.wastecorp.com

E-mail info@wastecorp.com



Mud Sucker B Series pumps are designed and specified to pump landfill leachate, agricultural waste, select manure pumping applications, mining waste, bauxite waste pumping, waste oil, biodiesel applications, coal slurry, tar sands applications, aquaculture, industrial fluids and more. Consult factory with flow rates and percentage of solids you are pumping before ordering. © Wastecorp, no reproduction without authorization

ACCESSORIES

響

	Part no.	Description		Part no.	Description
	19022-00	Recommended! Pressure relief valve, bronze set at 40 psi		61315-00	Wheel mount kit with handles
	63166-00	Basic spare parts kit (diaphragm and flappers)		63165-00	Comprehensive spare parts kit (diaphragm, flap- pers gaskets, weights and hardware)
	60718-00	Non-collapsible EPDM hose 2"x20'. Camlocks included		Various	Wet section coatings for specific applications
	51333-10	Discharge hose, lay flat (brown) 2"x50'. Camlocks included		62304-00	SEW MoviMot 24V key pad speed control
A STATE	34383-00	Stainer, sq. hole (solids) 2" FNPT	•	61492-00	Starter Control Panel w/ NEMA 12 protection
No. A	61387-00	Universal sewer adapter assem- bly		61491-00	Transformer start/estop, w/ Nema 12 overload protection
	60536-00	Clear swing check valve 2" FPTxFPT		62974-00	3-way brass valve w/ aluminum camlocks
P	60270-00	Camlock fitting 3" alum. male adapter MNPT	J	60506-00	The Gulper™ Suction tool No more bending
	61813-00	Gauge, 0-160 PSI (air models only)		61755-00	3-pc combo/regulator/ lubricator/filter/ mounting bracket (air models only)
No image available	62534-00	Ball valve 1/4" FNPT (air models only)			